

PERFORMANS DEĞERLERİ

			S1
10/45°C	90°C	Q(Kw)	222,4
		M(lt/h)	5447
	80°C	Q(Kw)	179,6
		M(lt/h)	4400
	70°C	Q(Kw)	139,6
		M(lt/h)	3420
10/60°C	90°C	Q(Kw)	201,4
		M(lt/h)	3452
	80°C	Q(Kw)	158,6
		M(lt/h)	2719
	70°C	Q(Kw)	118,5
		M(lt/h)	2033

NET LİTRE	1946 lt
BÜRÜT AĞIRLIK	 kg
NET AĞIRLIK	 kg
PALET	1310X1310X150 mm

Heat coil Maximum Operating Temperature 100°C

Heat coil Maximum Operating Pressure 8 bar

Domestic Hot Water Maximum Operating Temperature 95°C

Domestic Hot Water Maximum Operating Pressure 10 bar

ÜRÜN TEKNİK BİLGİ

TANIM	KOD	YÜKSEKLİK	INC
SOGUK SU GİRİŞ	B1	442 mm	11/4"
SERPANTİN GİRİŞ/ÇIKIŞ	B2 B5	534 mm 1261 mm	11/4"
RE SİRKÜLASYON	B4	907 mm	11/4"
SENSÖR	B3 B6	907 mm 1588 mm	1/2"
SICAK SU ÇIKIŞ	B7	1845 mm	11/4"
TEMİZLEME FLANŞI	B8	488 mm	4"
REZİSTANS GİRİŞİ	B9	1352 mm	2"
TERMOMETRE	B10	1837 mm	1/2"
MAGNEZYUM ANOT	B11	-----	11/4"
BOŞALTMA TAPASI	B12	-----	11/4"
ÜRÜN YÜKSEKLİĞİ	B13	2265 mm	-----
ÜRÜN ÇAPI	B14	1310 mm	-----


K-Q
TSE-ISO-EN
9001:2015
KALİTE YÖNETİM SİSTEMİ
BELGESİNE SAHİP
KURULUŞTA ÜRETİLMİŞTİR
EN ISO 9001:2015
QUALITY MANAGEMENT
SYSTEM CERTIFICATED



Made in TURKEY



ÜRÜN TEKNİK BİLGİ



MATERIAL: DD11/ ST37 SHEET

THICKNESS

SHEET	5 MM
CAMBER	6 MM
ANODE	DIN 4753-3 STANDART magnesium anode Ø26 MM X 700 MM
COATING 1	80 MM FOAM FAUX LEATHER

Dimensions without tolerance
ISO 2768-m

2000 LT TEK SERPANTİN BOYLER
BMM DP 2000ELG SNG TSB

TSE - 736 STANDARTLARINA GÖRE
TASARLANMIŞTIR.

SERPANTİN GENEL BİLGİLERİ

	S1
NET BOYU	39,5 Metre
YÜZEY ALANI	5,25 m2
DIŞ ÇAPI	42 mm
ET KALINLIĞI	3 mm
SU HACMİ	40 lt