

PERFORMANS DEĞERLERİ

S1			
10/45°C	90°C	Q(Kw)	108,8
		M(lt/h)	2666
	80°C	Q(Kw)	87,9
		M(lt/h)	2154
	70°C	Q(Kw)	68,3
		M(lt/h)	1674
10/60°C	90°C	Q(Kw)	98,5
		M(lt/h)	1690
	80°C	Q(Kw)	77,6
		M(lt/h)	1331
	70°C	Q(Kw)	58
		M(lt/h)	995

NET LİTRE	748 lt
BÜRÜT AĞIRLIK	 kg
NET AĞIRLIK	 kg
PALET	1000X1000X140 mm

Heat coil Maximum Operating Temperature 100°C

Heat coil Maximum Operating Pressure 8 bar

Domestic Hot Water Maximum Operating Temperature 95°C

Domestic Hot Water Maximum Operating Pressure 10 bar

ÜRÜN TEKNİK BİLGİ

TANIM	KOD	YÜKSEKLİK	INC
SOGUK SU GİRİŞ	B1	355 mm	11/4"
SERPANTİN GİRİŞ/ÇIKIŞ	B2 B5	437 mm 997 mm	11/4"
RE SİRKÜLASYON	B4	718 mm	11/4"
SENSÖR	B3 B6	515 mm 1255 mm	1/2"
SICAK SU ÇIKIŞ	B7	1653 mm	11/4"
TEMİZLEME FLANŞI	B8	372 mm	4"
REZİSTANS GİRİŞİ	B9	1052 mm	2"
TERMOMETRE	B10	1470 mm	1/2"
MAGNEZYUM ANOT	B11	-----	11/4"
BOŞALTMA TAPASI	B12	-----	11/4"
ÜRÜN YÜKSEKLİĞİ	B13	1830 mm	-----
ÜRÜN ÇAPI	B14	960 mm	-----


K-Q
TSE-ISO-EN
9001:2015
KALİTE YÖNETİM SİSTEMİ
BELGESİNE SAHİP
KURULUŞTA ÜRETİLMİŞTİR
EN ISO 9001:2015
QUALITY MANAGEMENT
SYSTEM CERTIFICATED



Made in TURKEY



ÜRÜN TEKNİK BİLGİ



MATERIAL: DD11/ ST37 SHEET

THICKNESS	
SHEET	4 MM
CAMBER	5 MM
ANODE	DIN 4753-3 STANDART magnesium anode Ø26 MM X 700 MM
COATING 1	80 MM FOAM FAUX LEATHER

Dimensions without tolerance
ISO 2768-m

800 lt TEK SERPANTİN BOYLER
BMM DP 800ELG SNG TSB

TSE - 736 STANDARTLARINA GÖRE
TASARLANMIŞTIR.

SERPANTİN GENEL BİLGİLERİ

	S1
NET BOYU	19,3 Metre
YÜZEY ALANI	2,57 m2
DIŞ ÇAPI	42 mm
ET KALINLIĞI	3 mm
SU HACMİ	19,7 lt