

PERFORMANS DEĞERLERİ

10/45°C	90°C	Q(Kw)	41,5
		M(lt/h)	1016
	80°C	Q(Kw)	33,5
		M(lt/h)	821,4
	70°C	Q(Kw)	26,0
		M(lt/h)	638,4
10/60°C	90°C	Q(Kw)	37,5
		M(lt/h)	644
	80°C	Q(Kw)	29,6
		M(lt/h)	507,6
	70°C	Q(Kw)	22,1
		M(lt/h)	379,5

NET LİTRE	280 lt
BÜRÜT AĞIRLIK	 kg
NET AĞIRLIK	 kg
PALET	710X610X120 mm

Heat coil Maximum Operating Temperature 100°C

Heat coil Maximum Operating Pressure 8 bar

Domestic Hot Water Maximum Operating Temperature 95°C

Domestic Hot Water Maximum Operating Pressure 10 bar

ÜRÜN TEKNİK BİLGİ

TANIM	KOD	YÜKSEKLİK	INC
SOGUK SU GİRİŞ	B1	252 mm	1"
SERPANTİN GİRİŞ/ÇIKIŞ	B2 B5	341 mm 675 mm	1 1/4"
RE SİRKÜLASYON	B4	547 mm	1"
SENSÖR	B3 B6	430 mm 1104 mm	1/2"
SICAK SU ÇIKIŞ	B7	1216 mm	1"
TEMİZLEME FLANŞI	B8	285 mm	4"
REZİSTANS GİRİŞİ	B9	750 mm	1 1/2"
TERMOMETRE	B10	1166 mm	1/2"
MAGNEZYUM ANOT	B11	-----	1"
BOŞALTMA TAPASI	B12	-----	1"
ÜRÜN YÜKSEKLİĞİ	B13	1425 mm	-----
ÜRÜN ÇAPI	B14	640 mm	-----


K-Q
TSE-ISO-EN
9001:2015
KALİTE YÖNETİM SİSTEMİ
BELGESİNE SAHİP
KURULUŞTA ÜRETİLMİŞTİR
EN ISO 9001:2015
QUALITY MANAGEMENT
SYSTEM CERTIFICATED



Made in TURKEY



ÜRÜN TEKNİK BİLGİ



MATERIAL: DD11/ ST37 SHEET

THICKNESS

SHEET	3 MM
CAMBER	3 MM
ANODE	DIN 4753-3 STANDART magnesium anode Ø26 MM X 350 MM
COATING 1	50 MM FOAM FAUX LEATHER

Dimensions without tolerance
ISO 2768-m

300 lt TEK SERPANTİN BOYLER
BMM DP 300ELG SNG TSB

TSE - 736 STANDARTLARINA GÖRE
TASARLANMIŞTIR.

SERPANTİN GENEL BİLGİLERİ

	S1
NET BOYU	7,4 Metre
YÜZEY ALANI	0,98 m2
DIŞ ÇAPI	42 mm
ET KALINLIĞI	3 mm
SU HACMİ	7,5 lt